

Dean, Ouisha <ouisha.dean@solvay.com>

FW: Message from KMBT C253

3 messages

Tim Martin <tmartin@airsci.com>

To: "Toenyes, Ouisha" <ouisha.toenyes@solvay.com>

Fri, Mar 23, 2012 at 1:36 PM

Ousiha.

Please see page 4 of the attached December 18, 2009 permit application (AP-10253) for the flare exit velocity of 52.9 m/sec that we discussed on the phone.


-Tim

From: portland@airsci.com [mailto:portland@airsci.com]

Sent: Friday, March 23, 2012 2:28 PM

To: tmartin@airsci.com

Subject: Message from KMBT C253



Toenyes, Ouisha <ouisha.toenyes@solvay.com>
To: Tim Martin <tmartin@airsci.com>

Fri, Mar 23, 2012 at 2:00 PM

Tim,

Thanks for scanning that permit. Also, I did forget to tell you that I was told by the mine department that the Katolight Generator does have an exit velocity of 940 degrees Fahrenheit.

-Ouisha

[Quoted text hidden]

_

Ouisha Toenyes Environmental Engineer (307) 872 - 6571 ouisha.toenyes@solvay.com

Fri, Mar 23, 2012 at 2:10 PM

To: "Toenyes, Ouisha" <ouisha.toenyes@solvay.com>

Ouisha,

Thanks for the additional information in the Katolight. I'll incorporate this information into the roster workbook and will send a copy back to you for your records when we make the estimates on the remaining missing information. If for some reason information does become available for E4, E5, the Katolight, and the reboilers, please send it along. Otherwise, we will be working with the data limitations on this end.

Have a good weekend.

-Tim

From: Toenyes, Ouisha [mailto:ouisha.toenyes@solvay.com]

Sent: Friday, March 23, 2012 1:00 PM

To: Tim Martin

Subject: Re: FW: Message from KMBT_C253

[Quoted text hidden]

This e-mail is confidential. If you are not the addressee or an authorized recipient of this message, any distribution, copying, publication or use of this information for any purpose is prohibited. Please notify the sender immediately by e-mail and then delete this message.

Ce message est confidentiel. Si vous n'etes pas le destinataire designe de ce message ou une personne autorisee a l'utiliser, toute distribution, copie, publication ou usage a quelques fins que ce soit des informations contenues dans ce message sont interdits. Merci d'informer immediatement l'expediteur par messagerie electronique et d'ensuite detruire ce message.

Department of Environmental Quality

Division of Air Quality

Permit Application

Date of Application: December 18, 2009

1.	Company Name: Solvay Chemicals, Inc.
2.	Mailing Address: P.O. Box 1167 (400 County Rd 85) Green River, Sweetwater County, Wyoming 82935 (307) 875-6500
3.	Plant Location: NE 1/4 of Section 31, Township 18 North, Range 109 West Sweetwater County, Wyoming (307) 875-6500
4.	Name of Owner or company official to contact regarding air pollution matters: Ronald O. Hughes Senior Vice President – Site Manager P.O. Box 1167 Green River, Wyoming 82935 (307) 875-6500
5.	General nature of business: Trona mine and refinery, producing soda ash and other sodium-based products
6.	Permit application is made for:
	X New construction Modification
	Relocation Operation
7.	Type of equipment to be constructed, modified, or relocated. (Please list each <u>major</u> piece of equipment separately.)
	2 Mine Vent Gas powered engines Mine Vent Gas flare Mine Vent Gas compressor
8.	If application is being made for operation of an existing source in a new location, list previous location and new location: N/A
	Previous location:
	New location:
9.	If application is being made for a crushing unit, is there: No open crushing
	Primary crushing Control equipment
	Secondary crushing Control equipment
	Tertiary crushing Control equipment
	Recrushing & Screening Control equipment

Page #2

\sim	
On	- ALEX TO 5
	veving

Control equipment

Drying

Control equipment

Other

Control equipment

Proposed dates of operation (month/year) Operations are scheduled to commence immediately upon issuance of permit.

10. Materials used in unit or process (include solid fuels):

Type of Material	Process Weight Average (lb/hr)	Process Weight Maximum (lb/hr)	Quantity/Year (tons/year)

11. Air contaminants emitted:

Emission Point	Pollutant	lb/hr	ton/yr	Basis of Data
75 HP Engine	NOx	0.17	0.74	Manufacturer Guarantee
	СО	0.17	0.74	Manufacturer Guarantee
	VOC	0.08	0.35	Manufacturer Guarantee
145 HP Engine	NOx	0.32	1.40	Manufacturer Guarantee
	СО	0.32	1.40	Manufacturer Guarantee
	VOC	0.16	0.70	Manufacturer Guarantee
Mine Vent Gas Compressor	NOx	0.88	3.85	Manufacturer Guarantee
	CO	0.88	3.85	Manufacturer Guarantee
	VOC	0.44	1.93	Manufacturer Guarantee
Mine Vent Gas Flare	NOx	5.86	25.67	Manufacturer Guarantee
	СО	342	14.98	Manufacturer Guarantee
	VOC	0.82	3.61	Manufacturer Guarantee

12. Air contaminant control equipment:

Emission Point	Туре	Pollutant Removed	Efficiency
75 HP Engine	AFR Controller NOx		74%
	NSCR Catalyst		7 170
145 HP Engine	AFR Controller	NOx	91%
	NSCR Catalyst	20 6 5 5 5	21/0
Mine Vent Gas	AFR Controller	NOx	*
Compressor	NSCR Catalyst		
Mine Vent Gas Flare	Low NOx Burners	NOx	57%
Mine Vent Gas Flare	Flare	VOC	99.0%

^{*} Efficiency for the Mine Vent Gas Compressor will be submitted under separate cover once compressor has been ordered.

13.	Type of	f combustion unit: (check if applicable):
	A.	Coal
		1. Pulverized:
		General; Dry Bottom; Wet Bottom; With Flyash Reinjection; Without Flyash Reinjection;
		2. Spreader Stoker:
		With Flyash Reinjection; Without Flyash Reinjection; Cyclone; Hand-Fired; Other;
	B. Fuel	Oil
	Horizont	tally Fired; Tangentially Fired;
	C. Natu	ral Gas
]	D. If oth	ner, please specify Mine Vent Gas
Hourly fu	el consu	mption (estimate for new equipment)
Size of co	mbustio	n unitBTU heat input/hour

14. Operating Schedule: <u>24</u> hours/day; <u>7</u> days/week; <u>52</u> weeks/year.

Peak production season (if any): None

15. Fuel analysis:

	A. Coal	B. Fuel Oil	C. Natural Gas
% sulfur			0.0
% ash			0.0
BTU Value			944 BTU/SCF

16. Products of process or units:

Products	Quantity/Year

17. Emissions to the atmosphere (each point of emission should be listed separately and numbered so that it can be located on the flow sheet):

Emission Point	Stack Height (ft)	Stack Diameter (ft)	Gas Discharged DSCFM (ACFM)	Exit Temp (°F)	Gas Velocity (ft/s)
Zenith	6.5	0.16	102 (578)	1420	479
Caterpillar	8.5	0.33	157 (643)	1063	380
Compressor Engine		This informati	on will be submitted un	der separate co	ver.
Flare	22	8.5	28,046 (180,328)	1800	52.9

^{*}Emissions for the Compressor Engine will be submitted under separate cover once compressor has been ordered.

18.	Does the input material o become airborne?	r product from this process or unit contain finely divided materials which	could

___ Yes ___X_ No

Is this material stored in piles or in some other way as to make	possible the creation of dust problems?
J	possione the creation of this month,

___ Yes __X_ No

List storage piles (if any):

Type of Material	Particle Size (Diameter or Screen Size)	Pile Size (Average Tons on Pile)	Pile Wetted (Yes or No)	Pile Covered (Yes or No)

- 19. Using a flow diagram:
 - (1) Illustrate input of raw materials.
 - (2) Label production processes, process fuel combustion, process equipment, and air pollution control equipment.
 - (3) Illustrate locations of air contaminant release so that emission points under items 11, 12 and 17 can be identified. For refineries, show normal pressure relief and venting systems. Attach extra pages as needed. Attach extra pages as needed.
- A site map should be included indicating the layout of facility at the site. All buildings, pieces of equipment, roads, pits, rivers and other such items should be shown on the layout.
- A location drawing should be included indicating location of the facility with respect to prominent highways, cities, towns, or other facilities (include UTM coordinates).

Certification

"I certify to the accuracy of the plans, specifications, and supplementary data submitted with this application. It is my opinion that any new equipment installed in accordance with these submitted plans and operated in accordance with the manufacturer's recommendations will meet emission limitations specified in the Wyoming Air Quality Standards and Regulations."

Signature	72.4/-				
Typed Name	Ronald O. Hughes				
Title	Senior Vice President – Site Manager				
Company	Solvay Chemicals, Inc.				
Mailing Address	P.O. Box 1167, Green River, Wyoming 82935				
Telephone					
P.E. Registration (if applicable)N/A					
State where registered					

GVBH Emission Calculations

GVBH E	Ingine	75	5 hp		
2000	g/bhp-hr	lb/hr	ton/yr	1 engine(s)	
NOx	1	0.17	0.74	0.74	
CO	1	0.17	0.74	0.74	
VOC	0.5	0.08	0.35	0.35	
GVBH E	ngine	145	hp		
	g/bhp-hr	lb/hr	ton/yr	1 opging(s)	
NOx	1	0.32	1.40	1 engine(s) 1.40	
co	i	0.32	1.40		
VOC	0.5	0.16	0.70	1.40 0.70	
				55	
Flare		2,200	ACFM	1,725	SCFM 944 BTU/SCF
				,	97.7 MMBTU/h
	lb/MMBTU	lb/hr	ton/yr	1 flare(s)	
NOx	0.06	5.86	25.67	25.67	
CO	0.035	3.42	14.98	14.98	
VOC	0.008	0.82	3.61	3.61	99% destruction
Compress	oor Engine	400	·		

Compressor Engine		400		
	g/bhp-hr	lb/hr	ton/yr	1 engine(s)
NOx	1	0.88	3.85	3.85
CO	1	0.88	3.85	3.85
VOC	0.5	0.44	1.93	1.93

To	tal project
to	n/yr
NOx	31.67
CO	20.98
VOC	14.71
	NOx CO

adding 2.25 % of 361 t for venting GVB

^{*}Emission factors are Manufacturer Guaranteed emissions.

STATE OF WYOMING

Department of Environmental Quality - Air Quality Division *Permit Application*

Reciprocating Engine Form

	GENERAL INFORMATION						
Company Name: Solvay Chem	nicals, Inc			· · · · · · · · · · · · · · · · · · ·			
Facility Name: Solvay Chem	Facility Name: Solvay Chemicals, Inc						
		ENGIN	E DATA				
Manufacturer:	Z	enith		Т	ype of Engine:		
Model:	4 Stroke (Cycle: X	2 Strok	e Cycle:			
Model: 520-4 4 Stroke Cycle: X 2 Stroke Cycle: No. of Cylinders: 6							
Compression Ratio:	-				Fuel Data:		
Serial Number: SOL	<u>.07-01</u>		Coal Bed Me	ethane		Other: X	
Date Ordered:	*			ine Fuel	Fuel Gas Heati	ng Value	
Date Manufactured: 3/21/07 Consumption (BTU/scf) (BTU/bhp-hr): (BTU/scf)					BTU/scf)		
Nameplate ·	Site Rat	ing	Operating R	Range			
Horsepower: 75			max 75	5			
Speed (rpm): 1800	,						
Exhaust Stack Height (m):_	1.98	Diameter (m):_	0.05 Ten	np. (K):1	044 Veloci	ty(m/s):	
Nateunita							
NO	CO	EMISSION		VC.	l uc	шо	
NO _X	CO		VC		НС		
g/hp-hr lb/hr	g/hp-hr	lb/hr	g/hp-hr	lb/hr	g/hp-hr	lb/hr	
1	1		0.5		<u> </u>	<u> </u>	
Annual Operating Hours: 8760							
EMISSION CONTROL EQUIPMENT							
Lean Burn: NSCR Catalyst: X AFR controller: X SCR Catalyst:							
Oxidation Catalyst: Other: Describe:							
Best Available Control Technology control cost analysis attached: yes X no							
ADDITIONAL INFORMATION REQUIRED							
On separate sheets of paper, attach a copy of engine manufacturer's site rating, site emission estimates, general rating specification for engine model, and documentation of date of order and date of manufacture for each engine.							

FORM AQD-ENGINE Date: September 2008

STATE OF WYOMING

Department of Environmental Quality - Air Quality Division Permit Application

Reciprocating Engine Form

GENERAL INFORMATION							
Company Na	ame: Solvay Cher	nicals, Inc					
Facility Na	Facility Name: Solvav Chemicals, Inc						
			ENGI	NE DATA			
Manufacturer: Caterpillar					T	ype of Engine:	
	Model:	G:	3306	4 Stroke Cycle: X 2 Stroke Cycle:			
No. of Cylinders: 6							
Compression Ratio: 10:5:1 Fuel Data:							
Serial N	Tumber: <u>G6X05</u>	<u> 631</u>		Coal Bed Me	ethane		Other: X
Date C	ordered:				ine Fuel	Fuel Gas Heati	
Date Manufa	actured: 11/2	8008		(BTU/	umption bhp-hr): <u>777</u>	<u>75</u> (1	BTU/scf)
				O T			
	<u>Nameplate</u>	Site Rati		Operating F			
	ver: 145			max 15	0		
	om): 1800			0.10	(77)	OAC WALLS	116
	tack Height (m):	2.6	Diameter (m):_	<u>0.10</u> Ten	np. (K):	846 Velocii	ty(m/s): 116
Note in	Mist.		EMISSIO	NS DATA			
	NO _X	C		VO	OC	нс	но
g/hp-hr	lb/hr	g/hp-hr	lb/hr	g/hp-hr lb/hr		g/hp-hr	lb/hr
1		1		0.5			
Annual Operating Hours: 8760							
EMISSION CONTROL EQUIPMENT							
Lean Burn: NSCR Catalyst: X AFR controller: X SCR Catalyst:							
Oxidation							
Catalyst: Other: Describe:							
Best Available Control Technology control cost analysis attached: yes no X							
ADDITIONAL INFORMATION REQUIRED							
On separate sheets of paper, attach a copy of engine manufacturer's site rating, site emission estimates, general rating							
specification for engine model, and documentation of date of order and date of manufacture for each engine.							

FORM AQD-ENGINE Date: September 2008